

Koch Biokosil Cellars & building pedestal impregnation



Technical Data Sheet

Item No. 0328 - . 0329, date 01.01.2016, page 1 2, EN

application

Impregnation - seal u. Water repellents, improvers

Suitable for:

Residential Facilities, Warehouses, listed buildings, hospitals, nursing homes, kindergartens, schools.

Others		system	Lime + silicate system
For processing	done	Process	roll, brush, airless
Creating plots:	compelling	drying time	12 hours
Working temperature:	+ 10 ° C	consumption	---
Storage:	frost free	transport plate	deleted
Classification according to EC Waste Code	does not require labeling	Waste no.	(EAKV 2002): 31442
Oily surfaces	not suitable	cleaning tools	water
before use	stir vigorously with whisk	Material Safety Data Sheet:	note
Dilute	water	use	not intended for human consumption
paintings	1-3 x	density	ca.1,12g / ml
Customs tariff number	38249070	PH value	approximately 11.5
Plastic dispersion	0%	Solvent / VOC	0%
		Best before [date:	9 months, cooling, frost-free conditions

Surface must be: sound, clean, dry, absorbent, without silicone, without dust (see VOB) primer:

airless applications

See: Technical Leaflet Airless

consumption

For 2- 3 coats 400-800 ml / sqm, base redevelopment 1: 1 diluted with water

Process

Wet dilute in wet, first cut with 20% water. Protect from rain

Suitable for:

Residential Facilities, Warehouses, listed buildings, hospitals, nursing homes, kindergartens, schools.

product	interior	outside	abrasion class	hue
Cellars & building pedestal impregnation	X	X		Transparent

Suitable for:

Natural stone, sandstone, exposed masonry, Ytong, brick, brick, hollow block, concrete, slate, stone Split, Fliesesefugen, mineral plasters. Loam / colors, rehabilitation of residential sockets at Salpeterbefall.

X

Not suitable on:

poorly absorbent surfaces

Composition (all ingredients)

Mixture of water glass, water, Sol, soft soap, accompanied by various biological, mineral adjuvants (without plastic dispersion, solvent)

Processing on third-party products / use of third-party products

Because of the variety of products on the market own tests shall be performed by the processor to assess the compatibility with other products. Mixing with products that are alien to the system is not allowed!

identification

lovely	Xi	Irritating to skin	R38
Risk eye damage	S2	Not specify children.	S 24/25
Touch eyes, avoid skin	S 26	Avoid contact with eyes, rinse immediately with water and seek medical visit.	S 36/37/39
When working	Protective clothing, protective gloves, safety goggles, face protection.		

safety Notice

Covering: z. As glass, ceramics, wood, paint, brick, metal, etc.

Information describes exclusively the technical characteristics of the product / products. After our present knowledge. Make no assurance of properties within the meaning of the legal warranty regulations. Delivery specifications refer. The technical information has been prepared in accordance with the European legislation.

Technical Information Sheet, Issuing Company: Contact person:

Koch GmbH · Mörikestraße 23 · D74632 Neuenstein
Tel. (+49) 07942-941322

Email: kontakt@koch-farbenwerk.de · Internet www.koch-farbenwerk.eu