

Koch Biokosil natural stone Impregnation sealer



Technical Data Sheet

Item No. 0308 -. 0309, date 01.01.2016, page 1 - 2, EN

application

Power to the building material water repellent Weather resistant. Protects the building material from mold, moss, oil, grease and dirt infestation

Suitable for:

Residential Facilities, Warehouses, listed buildings, hospitals, nursing homes, kindergartens, schools.

Others

For processing	done	Process	rolling, brushing, spraying
Creating plots:	compelling	drying time	12 hours
Working temperature:	+ 10 ° C	consumption	-.
Storage:	frost free	transport plate	deleted
Classification according to	does not require labeling	Waste no.	(EAKV 2002): 31442
EC Waste Code	No. 31442	cleaning tools	water
Oily surfaces	not suitable	Material Safety Data Sheet:	note
before use	stir vigorously with whisk	use	not intended for human consumption
Dilute	Water up to a maximum 10%	density	ca.1,10g / ml
paintings	1-2 x	PH value	approximately 11.5
Customs tariff number	38249070	Solvent / VOC	0%
Plastic dispersion	0%	Best before [date:	9 months, cooling, frost-free conditions
Surface must be:	sound, clean, dry, absorbent, without silicone, without dust (see VOB) primer:		

consumption

Natural stone, sandstone, exposed masonry, Ytong, brick	300-500 ml / sqm	Brick, hollow block, slate, split stone, tile joints	150-300 ml / sqm
Fiber cement panels	200-300 ml / sqm		

airless applications

See: Technical Leaflet Airless

Suitable for:

Residential Facilities, Warehouses, listed buildings, hospitals, nursing homes, kindergartens, schools.

product	interior	outside	abrasion class	hue
0308 - 0309 Biokosil natural stone impregnating, sealing,	X	X		Transparent

Suitable for:

Natural stone, brick, clinker, Terrakottea, sandstone, exposed masonry, Ytong, brick, brick, hollow block, stone, concrete, slate, split stone, tile joints, fiber cement panels.	X
---	---

Not suitable on:

Poor or non-absorbent surface

Processing on third-party products / use of third-party products

Because of the variety of products on the market own tests shall be performed by the processor to assess the compatibility with other products.

Composition (all ingredients)

Mixture of water glass, water, Sol, soft soap, accompanied by various biological, mineral adjuvants (without plastic dispersion, solvent)

identification

lovely	Xi	Irritating to skin	R38
Risk eye damage	S2	Not specify children.	S 24/25
Touch eyes, avoid skin	S 26	Avoid contact with eyes, rinse immediately with water and seek medical visit.	S 36/37/39
When working	Protective clothing, protective gloves, safety goggles, face protection.		

safety Notice

Covering: z. As glass, ceramics, wood, paint, brick, metal, etc.

Information describes exclusively the technical characteristics of the product / products. After our present knowledge. Make no assurance of properties within the meaning of the legal warranty regulations. Delivery specifications refer. The technical information has been prepared in accordance with the European legislation.

Technical Information Sheet, Issuing Company: Contact person:

Koch GmbH · Mörikestraße 23 · D74632 Neuenstein

Tel. (+49) 07942-941322

Email: kontakt@koch-farbenwerk.de · Internet www.koch-farbenwerk.eu