

No. 0215 **KOCH Bio Kalk Roll & Streichputz**
KOCH Organic lime plank plaster



Technical Data Sheet

Item No. 0215 -. 0220, 0938-0940 Date 11/06/2013, EN

| Others | | System | Lime - System |
|---|---|--------------------------------|---|
| Quality: | DIN 55946 | Process | rolling, brushing, airless |
| For processing | ready | If then dilute with mandatory: | Koch lime sinter water up to 5% was unless tinted |
| Creating plots: | compellingly | Drying time | 12 Hours |
| Working temperature: | + 10 ° C | Consumption | From 0.40 to 0.5 kg / sq.. |
| Storage: | Frost Free | Transport Plate | eliminates |
| Classification according to EC Waste Code | does not require labeling | Waste code no. | (EAKV 2002): 080112 |
| Oily Substrates | not suitable | Cleaning tools | Water |
| before use | stir vigorously with whisk | Material Safety Data Sheet: | note |
| Paintings | 1-2 x | Use | not intended for human consumption |
| EU Customs tariff number | 32149000 | PH value | approximately 12 |
| Solvent / VOC | 0% | Density | 1.55 g / ml |
| Best before [date: | 9 months, cool, frost-free conditions | Plastic dispersion | 0% |
| Tone down | Exclusively with No. 0603 -. 0760 KOCH universal tinting concentrate (alkaline compatible) a maximum of 5%. With tinted lime plasters a roll cloud formation is normal. Tinted plaster must not be diluted. | | |
| Surface must be: | sound, clean, dry, without wax without silicone, without dust (see VOB) primer: | | |

Suitable for:

Residential premises, Warehouses, listed buildings, hospitals, nursing homes, kindergartens, schools.

Airless Applications

See: Airless Technical Data Sheet

| Plaster | Interior | suitable for allergy sufferers | Abrasion class | Opacity | Hue |
|-------------------------------------|----------|--------------------------------|----------------|---------|----------------------|
| No. 0215 Organic lime plank plaster | X | X | | 2 | White, RAL 9010 matt |

Plaster

strong anti-fungal

No. 0215 Organic lime plank plaster

X

| Suitable for: | imperative: No. 0470 KOCH Ecoprimer Silicate Primer | Or absolutely no. 0314 KOCH Ecoprimer Sil swipe primer | or required no. 0377 KOCH Ecoprimer silicate bonding & blocking primer |
|--|---|--|--|
| Lime plasters, cement plasters, absorbent natural stones, clay plaster, gypsum plaster, plasterboard | X | | |
| Old coatings: plastic emulsion paints, silicone resin emulsion paints, mineral based, natural resin paints | | | X |
| Old coating: whitewash, clay color | X | X | X |

Crumbling underground:

Pre-treat with no. 0407 KOCH Ecoprimer FixActive.

Uneven surfaces:

Smooth with no. 0205 Koch restorer Bio Lime Stucco Creativ (putty)

Not suitable on:

Latex paint, poorly absorbent substrates, wallpaper, non-woven wallpaper

Processing to third-party products / use of third-party products

Because of the variety of products on the market own tests must be carried out by the processor to assess the compatibility with other products. Mixing with products that are alien to the system is not permitted! The same goes for cooking Farbenwerk products that are not part of the lime-system.

Composition (all ingredients)

marble lime putty, chalk, sand, vegetable starch, titanium dioxide, methylcellulose, water and a variety of natural plant oils without plastic dispersion

Identification

| | | | |
|------------------------|--|---|------------|
| Lovely | Xi | Irritant to skin | R38 |
| Risk eye damage | S2 | Do not give to children. | S 24/25 |
| Touch eyes, avoid skin | S 26 | Avoid contact with eyes, rinse immediately with water and seek medical visit. | S 36/37/39 |
| When working | Protective clothing, protective gloves, safety goggles, face protection. | | |

Safety note

Covering: z. As glass, ceramics, wood, paint, brick, metal, etc.

Information describes exclusively technical characteristics of the product / products. To the best of our knowledge. Offers no assurance of properties within the meaning of the legal warranty regulations. Delivery specifications refer. The technical information has been prepared in accordance with the European legislation.

Technical Information Sheet, Issuing Company: Contact person:

Koch GmbH · Mörikestraße 23 · D74632 Neuenstein

Tel. (+49) 07942-941322

Email: kontakt@koch-farbenwerk.de · Internet www.koch-farbenwerk.eu